

## Lightweight Pump

Powered by Honda's easy-starting, 31cc mini 4-stroke engine, this lightweight pump weighs only 15 lbs. and can pump up to 40 gpm. *Optional BH007 includes suction hose, strainer and garden hose coupler. Ship. wt. 17 lbs.*

**DON'T MISS**

More pumps on pages (p291 - 312)



- ▶ **Engine** - Honda 4-stroke, single-cylinder, air-cooled engine, GX31, 1.5 hp, OHV
- ▶ **Displacement** - 31cc
- ▶ **Bore and Stroke** - 1.5" x 1.0"
- ▶ **Compression Ratio** - 8:0:1
- ▶ **Pump Type** - General purpose, centrifugal, self-priming
- ▶ **Priming Time** - 120 sec @ 16.4"
- ▶ **Drive System** - Direct
- ▶ **Discharge Capacity** - 40 gal/min
- ▶ **Suction Port Diameter** - 1.0" NPT
- ▶ **Discharge Port Diameter** - 1.0" NPT
- ▶ **Total Head Lift** - 100'
- ▶ **Suction Head Lift** - 23'
- ▶ **Maximum Pressure** - 43 psi
- ▶ **Dimensions** - 13.0" x 9.8" x 12.8"
- ▶ **Dry Weight** - 15 lbs.

BB040	Lightweight Pump	\$349.95
BH007	Hose Kit *	\$105.95

\*Hose Kit Includes: 20 ft. suction hose, soft discharge hose, strainer

## General Purpose Pump

- ▶ **Performance** - Delivers a maximum discharge capacity of 275 gpm, maximum head of 85'
- ▶ **Engine** - Honda 4-stroke, single-cylinder, air-cooled engine, GX160, 5.5 hp, OHV
- ▶ **Displacement** - 163cc
- ▶ **Bore and Stroke** - 2.7" x 1.8"
- ▶ **Compression Ratio** - 8.5:1
- ▶ **Oil Alert®** - Standard
- ▶ **Pump Type** - Centrifugal, self-priming
- ▶ **Volute** - Rigid-mounted cast iron
- ▶ **Impeller** - Cast iron
- ▶ **Mechanical Seal** - Silicon carbide
- ▶ **Priming Time** - 150 sec @ 16.4"
- ▶ **Drive System** - Direct
- ▶ **Discharge Capacity** - 275 gal/min
- ▶ **Suction Port Diameter** - 3" NPT
- ▶ **Discharge Port Diameter** - 3" NPT
- ▶ **Total Head Lift** - 85'
- ▶ **Suction Head Lift** - 26'
- ▶ **Maximum Pressure** - 37 psi
- ▶ **Solids Handling** - 5/16"
- ▶ **Dimensions** - 20.1" x 15.2" x 17.9"
- ▶ **Dry Weight** - 60 lbs.

BB041	General Purpose Pump	\$545.95
BH008	Hose Kit *	\$230.95

\*Hose Kit Includes: 20 ft. suction hose, soft discharge hose, strainer



## "Mop-up" Dewatering Pump

**If You Need to Move 1,000 Gallons of Water Fast, We've Got the Pump for You!**

The "Mop-up" Pump is perfect for flat roofs, flooded garages and basements. Features a unique non-return valve built-in just below the impeller. Liquid will stay in the pump and pump-line after shut-down and not release out on the floor. The pump bottom is rubber clad to protect against damage to the floor surface. It will pump down to 1/12 of an inch, and start up in only a small puddle of liquid. Water cleanup after a fire is made easy with the "Mop-up" Pump. All pumps are equipped with thermal overload protection against overheating and delivered standard with 2" NPT connection. A Superior motor, with protection for longer life, less maintenance and less downtime! *Note: If the pump is to be used as a portable unit, it is strongly advised to add a "Ground Fault Interrupter" to the power supply line. Ship. wt. 27 lbs.*



AF412	"Mop-up" Dewatering Pump	\$527.95
-------	--------------------------	----------

## Honda Trash Pump

**NEW**

- ▶ Heavy-duty 3" construction trash pump
- ▶ Easy-starting Honda 11hp OHV commercial engine
- ▶ Full frame protection
- ▶ 319 gal./min. capacity
- ▶ Solid handling capability up to 1 1/16"
- ▶ Easy-to-use quick clean out port
- ▶ Easy-to-service impeller wear plate
- ▶ Protected by Honda Oil Alert®



BG155	Honda Trash Pump	\$1,664.95
BH008	Hose Kit *	\$230.95

\*Hose Kit Includes: 20 ft. suction hose, soft discharge hose, strainer